

How to pair your Smartcom to your new home Wi-fi

You will need

- Philips Screwdriver
- A pair of small step ladders (to reach near the alarm panel)
- Your mobile or tablet

Ready.....

- Locate the alarm panel. Next to this should be a small white box, this is Smartcom. Use the Phillips screwdriver to unscrew the bottom of the Smartcom.
- Lift the bottom lid to release. Your alarm will sound. Enter your user code into the keypad to silence the alarm.
- Look for the sticker with a barcode below the connectors.
- Take a clear picture of the sticker as you will need the codes. (Ideally on another phone / tablet)
- To the right hand side on the smartcom, press the little button for 10 seconds until the 2nd light from the left starts flashing slowly.
- On your mobile, go to settings and select Wi-fi.
- Your Smartcom should be showing under the network wi-fi list.
- Click on it and then enter the passphrase from the photo of the sticker.
- Open an internet browser on your mobile phone.
- In the web browser, type in the following IP address 192.168.2.1
- Under available wi-fi network, select you SSID from the list (your new home wi-fi)
- Enter your home wi-fi password in the box & press connect
- Ignore the Smartcom host wi-fi password and close the window

- Replace the Smartcom lid by ensuring it clips on at the top first then push down at the bottom.
- Type in the keypad your code & press the reset button.